



# HAULER<sup>®</sup> 800X

## UNMATCHED PERFORMANCE MEETS NON-STOP PRODUCTIVITY.

With an 8.4 cubic-foot cargo bed, bench seating, lifted suspension, and turf tires, every part of the Hauler 800X is designed to go the extra mile, then go 50 more. Available with your choice of a fuel-efficient 13.5 hp EFI gas engine or an ELiTE<sup>®</sup> lithium drivetrain powered by Samsung SDI battery technology, the Hauler 800X gives you the longest-lasting ride on the fairway.

**ELiTE<sup>®</sup>**  
LITHIUM

**8.4 CU FT**  
CARGO BED

**500 LB**  
TOWING CAPACITY

**725 LB**  
VEHICLE LOAD CAPACITY

**HIGHER**  
GROUND CLEARANCE

**ZERO  
MAINTENANCE**  
ELiTE LITHIUM BATTERY



# HAULER 800X

## HAULER 800X ELITE

## HAULER 800X GAS

### BODY & CHASSIS

FRAME	Welded Steel with E-Coat & DuraShield™ Powder Coat
BODY & FINISH	Injection Molded TPO
STANDARD COLOR	Forest Green

### DIMENSIONS

OVERALL LENGTH	110 in (279.4 cm)
OVERALL WIDTH	49 in (125 cm)
OVERALL HEIGHT	51 in (129.5 cm) ( w/o Roof) / 74 in (188 cm) (w/ Canopy)
WHEEL BASE	65.5 in (166.4 cm)
WHEEL TRACK	37 in (94 cm) Front / 38 in (96.5 cm) Rear
GROUND CLEARANCE	5.5 in (14.0 cm)
CARGO BOX CAPACITY	8.4 cu ft (0.24 cu m)
CARGO BOX DIMENSIONS	28.5 in (L) x 44.5 in (W) x 12 in (D) (72.4 cm x 113 cm x 30.5 cm)
CARGO BOX MATERIAL	Roto-Molded Polyethylene

### POWER

POWER TRAIN	56.7V Li-Ion Battery	4-Cycle, 24.5 cu in (401cc)
VALVE TRAIN	N/A	Single Cylinder OHV
HORSEPOWER (KW)	11.7 hp (8.7 kW) Peak	13.5 hp (10.1 kW)
ELECTRICAL SYSTEM	48V Primary, 12V Auxiliary	Starter/Generator. Solid State Reg.
BATTERY (QTY/TYPER)	2.2 Elite - Single Pack	One, 12V Maintenance Free
KEY OR PEDAL START		Pedal
AIR CLEANER	N/A	Replaceable Industrial Rated Dry Cartridge
LUBRICATION	N/A	Pressurized Oil System
OIL FILTER	N/A	Spin-On
COOLING SYSTEM	N/A	Air Cooled
FUEL CAPACITY	N/A	5.96 Gallon (22.6 L) tank
DRIVE TRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission
TRANSAXLE		Differential w/ Helical Gears
GEAR SELECTION	Dash Mount Forward-Neutral- Reverse / Key Switch	Forward - Reverse
REAR AXLE RATIO	16.99:1	11.47:1 (Forward) 14.35:1 (Reverse)

### PERFORMANCE

SEATING CAPACITY	2-Person (Bench)	
WEIGHT W/D BATTERIES	744 lb (351 kg)	800 lb (362.9 kg)
CURB WEIGHT	821 lb (372 kg)	830 lb (376 kg)
VEHICLE LOAD CAPACITY	725 lb (328.9 kg)	
BED LOAD CAPACITY	325 lb (147.4 kg)	
TOWING CAPACITY	500 lb (226.8 kg)	
OUTSIDE CLEARANCE CIRCLE	18.9 ft (5.8 m)	
SPEED	16.5 mph ± 0.5 mph (26.5 kph ± 0.8 kph)	

### STEERING & SUSPENSION

STEERING	Self-Compensating Rack and Pinion	
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers	
SERVICE BRAKE	Rear Wheel Mechanical Self-Adjusting Drum	
PARKING BRAKE	Automatic Electro-Magnetic	Self-Compensating, Single- Point Engagement
TIRES (FRONT & REAR)	20 x 8-10 (6 Ply Tires)	

### ELITE LITHIUM POWERTRAIN

- Zero Maintenance Battery
- 5-Year Battery Warranty
- Lightweight Footprint
- Increased Efficiency
- Upgrade to 6.2 Triple Pack for Extended Range
- Multifunction SOC/Speedometer Gauge
- Automatic Park Brake
- Limited Slip Differential

### OPTIONS & ACCESSORIES

- IntelliGauge™ (ELITE Only)
- 4-Wheel Mechanical Brakes
- Locking Glove Box
- Bed Dividers
- Floor Mount Attachment
- Windshield
- Canopy
- Electric Bed Lift
- Long-Handled Tool Holders
- Radio Holder
- Cargo Mesh Netting
- LED Headlights
- LED Taillights/Brake Lights
- Rearview Mirror
- USB Port
- Unique Key Switch
- Side Body Color
- Weather Enclosure
- ROPS-Certified Cab
- Ball Cage
- Hubcaps
- Rear Receiver Hitch
- Hour Meter
- Limited Slip Differential
- Rapid On-Board Charger
- Fuel/Oil Gauge

**CUSHMAN.COM**